

KEEP OUT OF REACH OF CHILDREN



HyGlo™

STAIN REMOVAL AGENT

For the removal of water staining of kiwifruit

A D D I T I V E

NET CONTENTS: 15 LITRES

PLEASE READ ENTIRE LABEL BEFORE MIXING OR USE

ACTIVE INGREDIENT: Contains 650 g/litre total acid equivalent of phosphate buffered lactic acid in the form of a soluble concentrate.

WARNING: May cause skin and eye irritation. Avoid contact with eyes and skin. In case of contact or spillage rinse immediately with plenty of water.

PERSONAL PROTECTION: Keep out of reach of children. When mixing wear a face shield. Use of protective clothing is recommended when spraying the dilute solution. Do not eat, drink or smoke while using. Triple rinse container and add residue to working tank. Dispose of container at an approved landfill or AgRecovery Depot. Avoid contamination of any water supply with chemical or empty container.

STORAGE: Store in original container out of reach of children.

SHELF LIFE: When stored appropriately this product should show no significant degradation for 2 years from date of manufacture. Contact your supplier for further information about the use of any product that is older than this.

SPRAYER DECONTAMINATION: Ensure the spray tank is thoroughly cleaned and drained before use. Decontaminate the tank by recirculating with 100-200 litres of standard HyGlo solution and pump to waste.

DIRECTIONS FOR USE			
CROP	USE	RATE	COMMENTS
Kiwifruit	Stain removal	500 ml/100L in 3000L/ha	Clean water must be used for spraying with HyGlo . Moderately hard water may be used but excessively hard water will reduce the effectiveness of HyGlo .

APPLICATION: Use HyGlo as a dilute spray to achieve very thorough spray coverage. Two spray runs (1500 litres/ha each) from opposite directions is strongly recommended. Apply **HyGlo** to dry fruit as close as is practicable to harvest. Allow sufficient time for fruit to completely dry before harvest. Flush the spray tank and equipment after applying **HyGlo**. Use 500 ml/100 litres of water. Pour the correct amount of **HyGlo** into the nearly filled tank and while agitating add the remainder of the water below the surface. Avoid air entrainment to reduce foaming.

RAINFALL: Rain after application may reduce effectiveness.

MATERIAL SAFETY DATA SHEET: Additional information is listed in the MSDS available from Zelam Limited or www.zelam.com

ERMA NEW ZEALAND: Additional information is available from the ERMA NZ website - www.ermanz.govt.nz. Approval Code: HSR002503

NOTICE TO BUYER: The manufacturer and vendors of **HyGlo** warrant the formulation to contain the specified active ingredients within accepted tolerance but make no warranty of any kind on the uses of material and accept no responsibility, whether the material is used in accordance with the label directions or not.

MANUFACTURED BY: Zelam Limited, Hudson Road,
New Plymouth, NZ.

Tel: 06 755-9234 Fax: 06 755-1174

™Registered trade name of Zelam Limited

EMERGENCY PHONE:
0800 CHEMCALL - 0800 243 6225

BATCH NO:
HyGlo

D.O.M:

